

TEST REPORT N. 54/10

Date of issue: 08/06/2010

Client: Geoplast SpA
Via Martiri della Libertà, 6/8 - Grantorto (PD)

Type of test: Measurement of the acoustic insulation of airborne noise according to the technical standard UNI EN ISO UNI EN ISO 140-4 (2000)

Test subject: Intermediate floor between the first floor and ground floor of multi-family residential building in via Santocchia a Foligno (PG)

Identification of partition: Slab between P1 attic bedroom unit on the first floor and master bedroom on the ground floor units T1

Construction characteristics:

- Plaster, 1 cm
- Lightened slab with elements Geoplast Nautilus 5 +16 +4 cm
- Lightweight concrete for fixture leveling, cm. 10-11
- Resilient material
- Self-leveling screed, 7-8 cm

Surface of the common partition: 9,6 sqm

Volume of the emitting room: 28 cu m

Volume of the receiving room: 28 cu m

Date of test: 04/06/2010

The stratigraphy of the partition test was declared by the Client

TEST REPORT N. 54/10
Measurement of the acoustic insulation of airborne noise

Client: Geoplast SpA - Via Martiri della Libertà, 6/8 - Grantorto (PD)
Date of issue: 08/06/2010 **Date of test:** 04/06/2010

Test conditions: The measurements were performed on a building under construction. Doors and windows apertures were plugged with plasterboard panels. As emitting room was chosen room on the first floor.

Instrumentation used:

- Bi-canal phonometer 01dB mod. Symphonie S/N 00882;
- Preamplifier ACLAN mod. PRE 12H S/N 00881;
- Microphone GRAS mod. 40AE S/N 166999;
- Preamplifier ACLAN mod. PRE 21A S/N 20312;
- Microphone Mikrotech Gefell mod. MK250 S/N 2888;
- Acoustic Calibrator ACLAN mod. CAL01 S/N 11038;
- Generator of noise dodecahedral Look Line mod. D301;

Certificates of calibration of the measuring system were issued on 20/5/10 by n. 164 (certificates n. F0516_10 e n. F0517_10) and in date 28/1/10 by n. 164 (certificate n. C0361_10).

Dettagli sull'esecuzione di prova:

In the emitting room, the noise machine was placed in two different positions at a distance greater of 1.4m and from the perimeter walls greater than 0.5 m. The two positions . The two positions do not identify any plane parallel to the walls. For each position were performed five measurements of the sound pressure level for bands of 1/3 octave in the emitting room and five in the receiving room. The microphone, mounted on the appropriate tripod, was placed in the receiving room in distinct points, distant from each other at least 0.7 m, at least 0.5 m away from the walls and 1 m from the emitting source. Were performed ten measurements of the sound pressure in the emitting room and ten in the receiving room, two by two together (emitting side and receiving side) with integration time always greater than 10 seconds. In the receiving room were also measured the level of background noise and reverberation time at various frequencies, repeating twice the test in at least three points, with the impulsive source method


Boundary conditions of the measurements: None
:

TEST REPORT N. 54/10

Measurement of the acoustic insulation of airborne noise

Client: Geoplast SpA - Via Martiri della Libertà, 6/8 - Grantorto (PD)
Date of issue: 08/06/2010 **Date of test:** 04/06/2010

1 - Average level of footsteps sound pressure measured in the emitting room (L_e)



STUDIO ING. VINCENZO BACCAN

industrial, architectural and environmental acoustics
Corso del Popolo, 161 - ROVIGO
info@studiobaccan.it

ing. Vincenzo Baccan


Page
n. 3 of 6

TEST REPORT N. 54/10

Measurement of the acoustic insulation of airborne noise

Client: Geoplast SpA - Via Martiri della Libertà, 6/8 - Grantorto (PD)
Date of issue: 08/06/2010 **Date of test:** 04/06/2010

2 - Average level of footsteps sound pressure measured in the receiving room (L_r)



STUDIO ING. VINCENZO BACCAN

industrial, architectural and environmental acoustics
Corso del Popolo, 161 - ROVIGO
info@studiobaccan.it

ing. Vincenzo Baccan


Page
n. 4 of 6

TEST REPORT N. 54/10
Measurement of the acoustic insulation of airborne noise

Client: Geoplast SpA - Via Martiri della Libertà, 6/8 - Grantorto (PD)
Date of issue: 08/06/2010 **Date of test:** 04/06/2010

3 - Average reverberation time measured in the receiving room (T_{rev})


Frequency f (Hz)	T_{rev} 1/3 octave (sec)
50	0,5
63	1,20
80	2,1
100	2,30
125	3,0
160	2,30
200	2,30
250	1,80
315	1,80
400	1,80
500	1,60
630	1,40
800	1,10
1.000	1,00
1.250	0,95
1.600	0,90
2.000	0,77
2.500	0,70
3.150	0,62
4.000	0,58
5.000	0,54



TEST REPORT N. 54/10
Measurement of the acoustic insulation of airborne noise

Client: Geoplast SpA - Via Martiri della Libertà, 6/8 - Grantorto (PD)
Date of issue: 08/06/2010 **Date of test:** 04/06/2010

4 - Evaluation index of the apparent airborne sound insulation (R'_w)



Evaluation index according to ISO 717-1:

$R'_w = 54$ dB

Terms of adaptation to the spectrum for pink noise and the noise from traffic :

$C = 0$ dB

$C_{tr} = -3$ dB

Assessment based on the results of measurements obtained by the third-octave by a method technical design

STUDIO ING. VINCENZO BACCAN

industrial, architectural and environmental acoustics
 Corso del Popolo, 161 - ROVIGO
 info@studiobaccan.it

ing. Vincenzo Baccan

Page
 n. 6 of 6